pipetman[®] M connected



CONNECTED VARIABLE VOLUME ELECTRONIC PIPETTES



| Make Manual Processes Verifiable

With PIPETMAN M Connected, open new possibilities in protocol execution assistance and data acquisition through the Bluetooth[®] connection.

| On-Target Performance

Trust in your results with guaranteed performance in both standard and repetitive pipetting mode.

Ease-of-Use

Save and transfer up to ten custom protocols from PIPETMAN M Software into your pipette. Executing protocols has never been so easy.



Pipette Smarter. Report Faster. Confidently.

 \ast



Wirelessly connect your electronic pipette to PIPETMAN M Software and Gilson applications.



Keep Track of Pipettes and Protocols Used

- Create your custom protocol on a PC or an Android tablet.
- Export your protocol steps for recording, reusing and sharing.
- | Never miss a service date. Your pipette stores this information in the software for you to recall.

PIPETMAN M Connected Single Channel					
Model		Part Number	Volume (µL)	PIPETMAN DIAMOND Tips	
P10M		F81040	0.5 - 10	D10 DL10	DF10 DFL10
P201	М	F81041	2 - 20	D200	DF30
P100	M	F81042	5 - 100	D200	DF100
P200	м	F81043	20 - 200	D200 D300	DF200 DF300
P300	м	F81044	20 - 300	D200* D300	DF200* DF300
P120	OM	F81045	100 - 1200	D1000* D1200	DF1000* DF1200
P500	оом	F81046	500 - 5000	D5000	
P10n	nLM	F81047	1 – 10 mL	D10mL	
PIPETMAN M Connected Multichannel					
P8x1	ом	F81048	0.5 - 10	D10 DL10	DF10 DFL10
P12x	10M	F81049			
P8x2	OM	F81050	1 - 20	DL10 D200	DFL10* DF30
P12x	20M	F81051			
P8x1	оом	F81052	10 - 100	D200	DF100
P12x	100M	F81053			
P8x200M P12x200M		F81054	20 - 200	D200 D300	DF100* DF200 DF300
		F81055			
P8x300M P12x300M		F81056	10 - 300	D200* D300	DF200* DF300
		F81057			
P8x1200M P12x1200M		F81058	50 - 1200	D1200	DF1200
		F81059			

Gilson maximum permissible errors are guaranteed only when PIPETMAN pipettes are used with the recommended PIPETMAN DIAMOND Tips. Visit <u>www.gilson.com/en/guaranteedperformance</u>.

Under these conditions, Gilson volumetric specifications in standard pipetting (PIPET mode) are guaranteed with a performance exceeding ISO 8655-2 recommendations for this mode.

*These PIPETMAN DIAMOND Tips can be used with the indicated pipettes for the REPETITIVE mode but not until the maximal volume of the pipette in PIPET mode. Please refer to the volume range of your tips. Recommended tips to get best results in REPETITIVE mode.

PIPETMAN M Connected specifications are downloadable from www.gilson.com/Specifications/PipetmanMConnected

www.gilson.com/ContactUs



LT800566 © 01/2018 Gilson S.A.S. All rights reserved. All trademarks are the property of Gilson, Inc. and its subsidiaries. This product and/or its use in certain methods is/are subject of patent rights including US patent #6.778.917, owned by EPPENDORF AG.

